


WISI MULTISYSTEM QUICK, cascadable 9 inputs




* Switches can be addressed with 14/18 V, 22 kHz
but only 4 inputs can be controlled
EMC acc. to CE, Class A


DY 04



DY 06



DY 08



Type	DY 04 Multiswitch, Stand Alone & cascadable	DY 06 Multiswitch, Stand Alone & cascadable	DY 08 Multiswitch, Stand Alone & cascadable
Trunk	Trunk	Trunk	Trunk
Inputs SAT + TERR	8 + 1	8 + 1	8 + 1
Frequency range TERR	5-862 MHz	5-862 MHz	5-862 MHz
Gain TERR	-	-	-
Output level TERR 3rd ord. EN 50083-3	-	-	-
Thru loss TERR:	6 dB	6 dB	6 dB
Frequency range SAT	950-2400 MHz	950-2400 MHz	950-2400 MHz
Gain SAT	15 dB	15 dB	15 dB
Output level SAT 3rd ord. EN 50083-3	111 dB μ V 35 dB IMA	111 dB μ V 35 dB IMA	111 dB μ V 35 dB IMA
Thru loss SAT	-	-	-
Cascadable with	DY94A-98A	DY94A-98A	DY94A-98A
Subscriber outputs	4	6	8
Frequency range	5-2400 MHz	5-2400 MHz	5-2400 MHz
Side loss TERR/SAT	22/0 dB	22/0 dB	22/0 dB
Isolation Subsc.-Subsc. TERR/SAT	>42/>30 dB	>42/30 dB	>42/>30 dB
Control signal	DiSEqC 2.0 *	DiSEqC 2.0 *	DiSEqC 2.0 *
Operating voltage	230 VAC,50/60 Hz	230 VAC,50/60 Hz	230 VAC,50/60 Hz
Power / current consumption	17.5 W/300 mA	17.5 W/300 mA	17.5 W/300 mA
LNB supply voltage	14 VDC/700 mA	14 VDC/700 mA	14 VDC/700 mA
Dimensions	210x140x55 mm	210x140x55 mm	210x140x55 mm
Packing unit	1 piece, 5.8 dm ³ , 0.95 kg	1 piece, 2.3 dm ³ , 1.13 kg	1 piece, 5,8 dm ³ , 0.95 kg
Shipping package	5 pieces, 30 dm ³ , 5 kg	5 pieces, 30 dm ³ , 5 kg	5 pieces, 30 dm ³ , 5 kg

